



## Yuasa Technical Data Sheet

### Yuasa YBX7027 - YBX7000 EFB Start Stop Plus Batteries

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

#### Performance

Voltage	12V
Capacity (20-hour)	65Ah
Cold Cranking Amps (EN1)	600A

#### Dimensions

Length	242mm
Width	175mm
Height	190mm

#### Weights & Measures

Mean Weight with Acid	16.6kg
-----------------------	--------



#### Container Features

Case Type	L2 DIN EFB
Terminal Type	T1
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid


#### Technology

Flame Arrestor Technology	✓
Separator	Ca/Ca
VDA Roll Over Test	PE
Recommended Charge Rate	✓
Performance Marking	4A
	W3-C2-V3-M1

#### Terminal Type

##### T1


Standard DIN Post



Positive Terminal

Negative Terminal


#### Cell Assembly Layout



0

#### Battery Hold-down

##### B3



Data Sheet generated on 30/01/2025 - E&OE